

imaf S.p.A

INDUSTRIA MATERIALI FOTOCHIMICI Via Galvani, 2 – 20068 Peschiera Borromeo (MI) Tel. 02/55 302 615 - Fax 02/55 302 643 Internet:www.imaf.it-E-mail: info@imaf.it

TECHNICAL SHEET

ACTIVAL

EMULSION FOR PREPARING AND WASHING OFFSET PRINTING PLATES $\underline{\textbf{ACTIVE}} \ \textbf{FORMULA}$

CHARACTERISTICS:

Solution aimed at removing surface oxidation from NOT printing areas and at regenerating printing areas of grained and anodized aluminium plates.

The newly developed formula allows to remove even persistent background fogs which may occur due to a not perfect preparation of the positive or negative plate.

Particularly suitable to prepare stored plates before printing.

APPLICATION:

Apply the product with a humid sponge on the interested areas. Wash off with water. SHAKE ALWAYS WELL BEFORE USE.

TECHNICAL DATA:

PHYSICAL STATE: Liquid
COLOUR: Pinky
PH 1
ODOUR: Typical

BOILING POINT: 1ypical 200° C
FLASH POINT: 63° C

WATER SOLUBILITY: Water emulsifiable

PRECAUTIONS:

Specifical product for analogue baked plates to be used, anyhow, with caution. Use it with digital plates, only if they have been baked.

With NOT baked digital plates, we recommend to use our product PREPARCLEANER A 21.

Since the product is slightly abrasive, do NOT wipe excessively during use.

PACKING:

Carton containing 6 cans of 2 litres